



High Security Seal · Data Sheet

Flexi Klick

High Security Container Bolt Seal

ISO 17712 "H" Compliant · C-TPAT Compliant

Because the pin of the Flexiklick is made from soft galvanized wire, the cut-off parts of the seal are much less likely to cause damage to truck tires compared to the rigid steel pins of traditional bolt seals. This feature brings cost savings to larger trucking companies and/or truck terminals, or any operational area where larger quantities of flexible bolt seals are being removed.

Compared to rigid steel bolt seals, the Flexi Klick is easier to cut when using a standard bolt cutter. It is the perfect security seal for organizations challenged with removing or applying larger volumes of security seals on a daily basis.

Features

- 1 Laser engraved dual numbering on both the pin and bush prevents parts substitution.
- 2 The anti-spin feature protects against friction attacks.
- 3 Compared to a rigid steel bolt seal, the Flexi Klick is safer to cut. The flexibility of the pin eliminates the ricochet or "bullet effect" created when most rigid steel bolt pins are cut by a bolt cutter.
- 4 The flexibility of the pin allows for easy application on container/trailer door latches that have been bent out of shape after years of use.
- 5 The extra long pin of the Flexi Klick makes this seal perfect for truck trailers with roll down door latches that require additional pin length.
- 6 The flexible pin made from galvanized wire provides excellent protection against crude tools such as hammers, crow bars and steel pipes. Upon impact, the pin will bend, not break.
- 7 The pin and bush are joined together for easy handling.

Technical Specifications

PRODUCT

Material	Pin Length	Bolt Diameter	Wire Diameter	Tensile Strength	Marking Area	Max Marking Digits
Plastic pin and barrel: ABS Pin and bush: Hardened Steel, Flexible Galvanized Steel Wire	92 mm	Ø 11.9 mm	Ø 5.0 mm	1300 kg/f	Pin: 5.0 x 17.0 mm Barrel: 16.0 x 27.0 mm	Serial no: 8

OUTER CARTON

Carton Quantity	Dimensions	Weight kg/carton	Volume m ³ /carton	Standard Colours
250 pcs	400 x 290 x 225 mm	15.01 kg	0.0261 m ³	



FMM EXCELLENCE AWARD 2012
QUEST FOR CONTINUOUS IMPROVEMENT
BEST MANUFACTURER IN MALAYSIA IN 2012